# Blackline F12<sup>+</sup>

Compact, two-way passive system

#### features

- Compact two-way passive system
- User rotatable 80° x 50° horn
- Top hat fitting for speaker stand mounting
- Five year limited warranty


### applications

- Live club performance
- Floor monitor
- Club installs
- AV presentations

The Blackline F12 $^+$  is a high power, compact two-way system with a new, vented-chassis, 12" (300mm) LF driver and a new 1" (25mm) exit compression driver mounted on a rotatable 80° x 50° constant directivity HF horn. The LF driver has a tough, water resistant cone and features a high BL motor with a flatwire copper coil and an aluminium demodulating ring. This reduces intermodulation distortion and improves midrange performance when driven hard. Increased excursion is available by virtue of a triple roll surround and deep motor structure. The directivity of the LF driver has been matched to the HF horn in the crossover region by improved crossover design and cone profile optimisation, also the new HF compression driver utilises an ultra-lightweight Kapton diaphragm for extended high frequency response.

A Martin Audio M3<sup>+</sup> or DX1 Electronic Controller is available to provide F12<sup>+</sup>/subwoofer crossover and limiter facilities.

#### overall dimensions





<u>F12+</u>



## technical specifications

| TYPE                   | Compact, two-way passive                       |
|------------------------|--|
| FREQUENCY RESPONSE (5) | $65Hz-18kHz \pm 3dB$                           |
|                        | -10dB @ 55Hz                                   |
| DRIVERS                | 12" (300mm)/2.5" (63.5mm) voice coil LF driver |
|                        | I" (25mm) exit HF compression driver           |
| RATED POWER (2)        | 300W AES, 1200W peak                           |
| RECOMMENDED AMPLIFIER  | 400W-1000W into 4 ohms                         |
| SENSITIVITY (6)        | 97dB   |
| MAXIMUM SPL (7)        | 120dB continuous, 126dB peak                   |
| NOMINAL IMPEDANCE      | 8 ohms   |
| DISPERSION (-6dB)      | 80° horizontal, 50° vertical                   |
| CROSSOVER              | 2.2 kHz passive                                |
| ENCLOSURE              | 38 litre, multi-laminate birch ply             |
| FINISH                 | Textured black paint                           |
| PROTECTIVE GRILLE      | Black perforated steel                         |
| CONNECTORS             | 2 x Neutrik NL4                                |
| PIN CONNECTIONS        | FR+,-: I+,I-, Link thro': 2+,2-                |
| FITTINGS               | 10 x M8, 4 x M8 threaded inserts               |
|                        | I x mounting pole socket                       |
|                        | I x pocket handle                              |
| DIMENSIONS             | (W) 398mm x (H) 571mm x (D) 365mm              |
|                        | (W) 15.6ins x (H) 22.5ins x (D) 14.3ins        |
| WEIGHT                 | 21kg (46lbs)                                   |

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HPI2 3SL, England.
Telephone: +44 (0)1494 533312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.

